

LA-UR-21-26722

Approved for public release; distribution is unlimited.

Title: Report to NCSP on FY21 DANCE and NEUANCE measurements of 233U(n,)

Author(s): Leal Cidoncha, Esther

Couture, Aaron Joseph

Intended for: Report

Issued: 2021-07-14



Report to NCSP on FY21 DANCE and NEUANCE measurements of $^{233}\mathrm{U}(n,\gamma)$

E. Leal Cidoncha and A. CoutureP-3Los Alamos National Laboratory

July 6, 2021

1 233 U samples

The 30 mg of ²³³U material were supplied from Oak Ridge National Laboratory, as a solid oxide, which isotopic composition is given in the table 1,

Isotope	Atom (%)
$^{233}{ m U}$	99.9843
$^{234}\mathrm{U}$	< 0.0002
$^{235}{ m U}$	0.0017
$^{236}{ m U}$	0.0004
$^{238}\mathrm{U}$	0.0134

Table 1: 233 U isotopic composition. There was a 232 U content of the 233 U material that was calculated to be less than 1 ppm.

The initial plan was to make one thick 10 mg U3 sample, however we could get enough material to produce two 233 U samples, of 20 mg and 10 mg, see figure 1. The two 233 U samples were produced at LANL¹ by stippling the 233 U in 0.3 mil Kapton foils, which has proved a robust, cost-effective method for producing actinide samples in the range of 1-20 mg in a small (<1 cm) diameter with very high efficiency.




Figure 1: ²³³U 10 mg sample (figure on the left), and 20 mg sample (figure on the right).

¹Prepared by Evelyn M. Bond at LANL.

2 Test of new ²³³U sample for DANCE Measurement

The test measurement was performed over 10 days with the 20 mg sample, and then the 10 mg sample was placed in the beam for 1 day. The rest of the beam time was used to measure radioactive γ sources for energy calibration, background measurements and tests to define the $^{233}\mathrm{U}$ windows required during the data taking, also some measurements were done with a $^{235}\mathrm{U}$ sample to cross-check the performance and the systematics. Based on the analysis of the test measurement data, we have determined that this pair of new, thick targets will be appropriate for completion of the cross section measurement with DANCE.



Figure 2: The NEUANCE instrument placed inside DANCE.

In order to complete the statistics needed above 10 keV, a production measurement of the 233 U capture cross section, using the thick target (\sim 20 mg) has been proposed for the CY21 runcycle. Through collaboration with the DANCE experimental team, we have arranged for the NEUANCE array to stay in place in the CY21 run cycle until the 233 U measurement is complete, further reducing systematic uncertainties in the measurement.

3 Conclusions and next steps

The experimental measurement is ready to be performed. The measured data will be then analyzed and used to increase the statistics together with the data measured in December 2020. Further steps on the analysis with the new experimental data will be presented in the next report.